NANO TECHNOLOGY
CHEMICALS

Safety Data Sheet

Mineral Spirits (Rule 66)

The pages that follow are the Safety Data Sheet as issued by the supplier/manufacturer. They are provided unchanged by Nano Technology Chemicals (NTC). Refer to Section 1 of the attached SDS for the responsible party and emergency telephone number.

Questions about this product or document:

Nano Technology Chemicals, Charlotte, NC
Phone: 704-659-3682
Email: sales@nanotechnologychemicals.com
Web: nanotechnologychemicals.com

Cover sheet date: October 12, 2026. For the SDS revision date, see the attached document.

In an emergency, use the emergency telephone number in Section 1 of the attached SDS.

Safety Data Sheet
Mineral Spirits 66 7.5%

Version 1.9 Revision Date: 10/28/2024

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Mineral Spirits 66 7.5%

Recommended use of the chemical and restrictions on use

Recommended use : SOLVENT

Manufacturer or supplier's details

Company : Univar Solutions USA
Address 3075 Highland Pkwy Suite 200
Downers Grove, IL 60515
United States of America (USA)

Emergency telephone number:
Transport North America: CHEMTREC (1-800-424-9300)
CHEMTREC INTERNATIONAL Tel # 703-527-3887

Additional Information: : Responsible Party: Product Compliance Department
E-mail: SDSNA@univarsolutions.com
SDS Requests: 1-855-429-2661
Website: www.univarsolutions.com

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids	:	Category 3
Skin irritation	:	Category 2
Eye irritation	:	Category 2A
Specific target organ toxicity - single exposure	:	Category 3 (Central nervous system)
Specific target organ toxicity - repeated exposure	:	Category 1
Aspiration hazard	:	Category 1

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H372 Causes damage to organs through prolonged or repeated exposure.

Precautionary statements : **Prevention:**
P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ eye protection/ face protection.
Response:
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P314 Get medical advice/ attention if you feel unwell.
P331 Do NOT induce vomiting.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
Storage:
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.
Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

CAS-No.	Chemical name	Weight percent
64742-47-8 / 64742-88-7	Distillates (pet), hydrotreated light AND/OR Solvent naphtha (pet), med aliph.	90 - 100

Mixture	C9-C15 Aromatics	10 - 20
25551-13-7	Benzene, trimethyl-	1 - 5
111-84-2	Nonane	1 - 5

Actual concentration is withheld as a trade secret
Any Concentration shown as a range is due to batch variation.

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.

In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO2)
Dry chemical

Unsuitable extinguishing media : High volume water jet

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Carbon oxides

No hazardous combustion products are known

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.

		Use a water spray to cool fully closed containers.
Special protective equipment for firefighters	:	Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	:	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	:	Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	:	Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.
Advice on safe handling	:	Avoid formation of aerosol. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.
Conditions for safe storage	:	No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

CAS-No.	Components	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
64742-47-8 / 64742-88-7	Distillates (pet), hydrotreated light AND/OR Solvent naphtha (pet), med aliph.	TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	200 mg/m3 (total hydrocarbon vapor)	ACGIH
		TWA	400 ppm 1,600 mg/m3	OSHA P0
25551-13-7	Benzene, trimethyl-	TWA	10 ppm	ACGIH
		TWA	25 ppm 125 mg/m3	OSHA P0
		PEL	25 ppm 125 mg/m3	CAL PEL
111-84-2	Nonane	TWA	200 ppm	ACGIH
		TWA	200 ppm 1,050 mg/m3	NIOSH REL
		TWA	200 ppm 1,050 mg/m3	OSHA P0
		PEL	200 ppm 1,050 mg/m3	CAL PEL

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required.
In the case of vapour formation use a respirator with an approved filter.
General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.
In the case of vapour formation use a respirator with an approved filter.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection	:	Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Hygiene measures	:	When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Colour	:	clear, transparent
Odour	:	characteristic, hydrocarbon-like, solvent-like
Odour Threshold	:	No data available
pH	:	Not applicable
Freezing Point (Melting point/freezing point)	:	No data available
Boiling Point (Boiling point/boiling range)	:	149 - 213 °C (300 - 415 °F)
Flash point	:	40 - 46 °C (104 - 115 °F) Method: Tag closed cup
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit	:	6 %(V)
Lower explosion limit	:	0.6 %(V)
Vapour pressure	:	< 1 mmHg @ 20 °C (68 °F)
Relative vapour density	:	5
Relative density	:	0.77 - 0.79 @ 15 °C (59 °F) Reference substance: (water = 1)
Density	:	0.79 g/cm3 @ 15 °C (59 °F) 6.44 lb/gal @ 15.56 °C (60.01 °F)
Solubility(ies)		
Water solubility	:	insoluble
Solubility in other solvents	:	soluble Solvent: Hydrocarbons
Partition coefficient: n-octanol/water	:	No data available
Auto-ignition temperature	:	230 - 270 °C
Thermal decomposition	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal use.

Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	No hazards to be specially mentioned. No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Oxidizing agents Strong acids strong alkalis Chlorine Oxygen None known.
Hazardous decomposition products	:	Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:

Acute oral toxicity	:	Acute toxicity estimate: > 5,000 mg/kg
Acute inhalation toxicity	:	Acute toxicity estimate: 110 mg/l Exposure time: 4 h Test atmosphere: vapour
Acute dermal toxicity	:	Acute toxicity estimate: > 5,000 mg/kg

Components:

64742-47-8 / 64742-88-7:

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	:	Remarks: No data available
Acute dermal toxicity	:	LD50 (Rabbit, male and female): > 2,000 mg/kg Assessment: The substance or mixture has no acute dermal toxicity

Mixture:

Acute inhalation toxicity	:	Assessment: The component/mixture is moderately toxic after short term inhalation.

25551-13-7:

Acute oral toxicity	:	LD50 (Rat): Assessment: The component/mixture is moderately toxic after single ingestion.
Acute dermal toxicity	:	Assessment: The component/mixture is moderately toxic after single contact with skin.

Remarks: No data available

Skin corrosion/irritation

Components:

64742-47-8 / 64742-88-7:
Species: Rabbit
Exposure time: 24 h
Result: Irritating to skin.

25551-13-7:
Species: Rabbit
Result: Irritating to skin.

111-84-2:
Species: Rabbit
Result: Irritating to skin.
Test substance:Information given is based on data obtained from similar substances.

Serious eye damage/eye irritation

Components:

64742-47-8 / 64742-88-7:
Species: Rabbit
Result: Irritating to eyes.

Mixture:
Result: Irritating to eyes.

25551-13-7:
Species: Rabbit
Result: Irritating to eyes.

Respiratory or skin sensitisation

Components:

64742-47-8 / 64742-88-7:
Test Type: Buehler Test
Species: Guinea pig
Result: Did not cause sensitisation on laboratory animals.

Germ cell mutagenicity

Components:

64742-47-8 / 64742-88-7:
Germ cell mutagenicity - Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

Carcinogenicity

Components:

64742-47-8 / 64742-88-7:

Carcinogenicity - Assessment	:	Not classifiable as a human carcinogen.
IARC		No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
OSHA		No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP		No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Components:

64742-47-8 / 64742-88-7:

Reproductive toxicity - Assessment		Animal testing did not show any effects on fertility.
Teratogenicity - Assessment	:	Embryotoxicity classification not possible from current data.

STOT - single exposure

Components:

64742-47-8 / 64742-88-7:
Exposure routes: Inhalation
Target Organs: Central nervous system
Assessment: May cause drowsiness or dizziness., The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

Mixture:
Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

111-84-2:
Target Organs: Central nervous system
Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

STOT - repeated exposure

Product:
Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 1.

Aspiration toxicity

Product:
May be fatal if swallowed and enters airways.

Components:

64742-47-8 / 64742-88-7:
May be fatal if swallowed and enters airways.
Mixture:
Aspiration Toxicity - Category 1
111-84-2:
May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Concentrations substantially above the TLV value may cause narcotic effects.
Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

64742-47-8 / 64742-88-7:

Toxicity to fish	:	LL50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l Exposure time: 96 h Test Type: semi-static test
Toxicity to daphnia and other aquatic invertebrates	:	EL50 (Daphnia magna (Water flea)): 1.4 mg/l Exposure time: 48 h Test Type: static test
Toxicity to algae	:	EL50 (Pseudokirchneriella subcapitata (green algae)): 1 mg/l End point: Growth rate Exposure time: 72 h Test Type: static test
Acute aquatic toxicity- Assessment	:	Toxic to aquatic life.
Chronic aquatic toxicity- Assessment	:	Toxic to aquatic life with long lasting effects.

111-84-2:

Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 0.2 mg/l Exposure time: 48 h Test Type: static test
M-Factor (Acute aquatic toxicity)	:	1
Chronic aquatic toxicity- Assessment	:	Very toxic to aquatic life with long lasting effects.

Persistence and degradability

Components:

64742-47-8 / 64742-88-7:

Biodegradability	:	aerobic

Biodegradation: 61 %
Exposure time: 28 d
Remarks: Readily biodegradable

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Ozone-Depletion Potential	:	Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).
Additional ecological information	:	An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues	:	Dispose of in accordance with all applicable local, state and federal regulations. For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Univar Solutions ChemCare: 1-800-637-7922
Contaminated packaging	:	Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

DOT (Department of Transportation):
UN1268, PETROLEUM DISTILLATES, N.O.S., 3, III

IATA (International Air Transport Association):
UN1268, PETROLEUM DISTILLATES, N.O.S., 3, III

IMDG (International Maritime Dangerous Goods):
UN1268, PETROLEUM DISTILLATES, N.O.S., 3, III, Marine Pollutant (MIXTURE OF PETROLEUM DISTILLATES) , Flash Point:40 - 46 °C(104 - 115 °F)

Special Notes: : The flash point for this material is greater than 100 °F (38 °C) and may be re-classified as "Combustible liquid" in accordance with 49 CFR 173.150(f). Therefore, non-bulk containers (<450L or <119 gallon capacity) of this material may be shipped as non-regulated when transported solely by land, as long as the material is not a hazardous waste, a marine pollutant, or specifically listed as a hazardous substance.

SECTION 15. REGULATORY INFORMATION

WHMIS Classification : B3: Combustible Liquid
D2B: Toxic Material Causing Other Toxic Effects

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
**Benzene	71-43-2	10	10101
**Naphthalene	91-20-3	100	101010

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Skin corrosion or irritation
Specific target organ toxicity (single or repeated exposure)
Aspiration hazard
Serious eye damage or eye irritation

SARA 302 : This material does not contain any components with a section 302 EHS TPQ.

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489).

Clean Water Act

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

108-88-3	**Toluene
71-43-2	**Benzene
100-41-4	**Ethylbenzene
91-20-3	**Naphthalene

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

108-88-3	**Toluene
71-43-2	**Benzene
100-41-4	**Ethylbenzene
91-20-3	**Naphthalene

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

Massachusetts Right To Know

25551-13-7	Benzene, trimethyl-
111-84-2	Nonane
71-43-2	**Benzene

Pennsylvania Right To Know

64742-47-8 / 64742-88-7	Distillates (pet), hydrotreated light AND/OR Solvent naphtha (pet), med aliph.
Mixture	C9-C15 Aromatics
25551-13-7	Benzene, trimethyl-
111-84-2	Nonane
98-82-8	**Cumene
108-88-3	**Toluene
71-43-2	**Benzene
100-41-4	**Ethylbenzene
91-20-3	**Naphthalene

California Prop 65


⚠ **WARNING**: This product can expose you to chemicals including **Cumene, **Benzene, **Ethylbenzene, **Naphthalene, which is/are known to the State of California to cause cancer, and **Toluene, **Benzene, **n-Hexane, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

TSCA	:	On TSCA Inventory
DSL	:	All components of this product are on the Canadian DSL
AICS	:	On the inventory, or in compliance with the inventory
NZIoC	:	On the inventory, or in compliance with the inventory
ENCS	:	On the inventory, or in compliance with the inventory
KECI	:	On the inventory, or in compliance with the inventory
PICCS	:	On the inventory, or in compliance with the inventory
IECSC	:	On the inventory, or in compliance with the inventory
Special Notes:	:	** Other substances in the product which may present a health or environmental hazard.

SECTION16. OTHER INFORMATION

NFPA:



HMIS III:

HEALTH	2/
FLAMMABILITY	3
PHYSICAL HAZARD	0

0 = not significant, 1 =Slight,
2 = Moderate, 3 = High
4 =Extreme, * = Chronic

The information accumulated is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made become available subsequently to the date hereof, we do not assume any responsibility for the results of its use. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Univar Solutions Product Compliance Department (1-855-429-2661) SDSNA@univarsolutions.com.

Revision Date : 10/28/2024

Legacy SDS: : R0000591

Material number:
16132092, 103646, 102989, 547277, 53764, 612976, 20087, 660347, 86313, 53281, 53768, 744414, 744413, 604767, 70884, 103635, 70230, 86310, 70887, 70876, 103643, 70239, 554091, 554080, 556672, 556673, 53226, 102363, 54498, 69659, 87259, 86529, 576791, 86524, 557932, 85978, 86519, 546934, 86534

Key or legend to abbreviations and acronyms used in the safety data sheet			
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenar-	OSHA	Occupational Safety & Health

	io Tool		Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		